www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO 2-CONDUCTOR/1-PIN GROUND CARRIER TERMINAL BLOCK; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; PUSH-IN CAGE CLAMP®; 2,50 MM²; GREEN-YELLOW

Ratings per: IEC/EN 60947-7-2;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Number of connection points (connection type): 2;
Tip actionare: Open Tool Slot; Push-in;
Connectable conductor materials: Copper;
Nominal cross-section: 2.5 mm²;
Solid conductor: 0.25 … 4 mm² / 22 … 12 AWG;
Solid conductor; push-in termination: 0.75 … 4 mm² / 18 … 12 AWG;
Fine-stranded conductor: 0.25 … 4 mm² / 22 … 12 AWG;
Fine-stranded conductor; with insulated ferrule: 1 … 2.5 mm² / 18 … 12 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 1 … 2.5 mm² / 18 … 12 AWG;
Strip length: 10 … 12 mm / 0.39 … 0.47 inch;
Number of connection points: 1;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;
Latime: 5.2 mm / 0.205 inch;
Inaltime from upper-edge of DIN-rail: 32.5 mm / 1.28 inch;
Adancime: 59.2 mm / 2.331 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;

Culoare: green-yellow;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,136; MJ
Greutate: 9,3; g
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4050821145165;
Customs tariff number: 85366990990;
Pret: 13,29 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/2-conductor-1-pin-ground-carrier-terminal-block-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-green-yellow-141811