



**WAGO 1-CONDUCTOR N-DISCONNECT TERMINAL BLOCK; 10 MM<sup>2</sup>; CAGE CLAMP®; 10,00 MM<sup>2</sup>; BLUE**

Tensiune nominala (III/3): 400; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 57; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Open Tool Slot;  
Connectable conductor materials: Copper;  
Solid conductor: 0,2 ... 10 mm<sup>2</sup> / 24 ... 8 AWG;  
Fine-stranded conductor: 0,2 ... 10 mm<sup>2</sup> / 24 ... 8 AWG;  
Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;  
Solid conductor 2: 0,2 ... 16 mm<sup>2</sup> / 24 ... 6 AWG;  
Fine-stranded conductor 2: 0,2 ... 16 mm<sup>2</sup> / 24 ... 6 AWG;  
Numar total de conexiuni: 1;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 10 mm / 0.394 inch;  
Inaltime from upper-edge of DIN-rail: 43,5 mm / 1.713 inch;  
Adancime: 82,5 mm / 3.248 inch;  
Design: angled;  
Tip montaj: DIN-35 rail;  
Marking level: Center marking;  
Culoare: blue;  
Greutate: 32,9; g  
Product Group: 17 (TOP JOB installation terminal blocks);  
Tip ambalare: BOX;

Tara de origine: PL;  
GTIN: 4045454016975;  
Customs tariff number: 85365080900;  
Pret: 22,61 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-n-disconnect-terminal-block-10-mm2-cage-clamp-10-00-mm2-blue-141886>