

WAGO 4-CONDUCTOR CHASSIS-MOUNT TERMINAL STRIP; 3-POLE; N-PE-L1; WITH GROUND CONTACT; 4 MM²; 4,00 MM²; BLACK

Tesiune nominala (III/3): 500; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 32; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Operating tool; Push-button;
Connectable conductor materials: Copper;
Solid conductor: 0,5 … 4 mm² / 20 … 12 AWG;
Solid conductor; push-in termination: 0,75 … 4 mm² / 18 … 12 AWG;
Stranded conductor: 0,5 … 4 mm² / 20 … 12 AWG;
Fine-stranded conductor: 0,5 … 4 mm² / 20 … 12 AWG;
Fine-stranded conductor; with insulated ferrule: 0,5 … 2,5 mm² / 20 … 12 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 0,75 mm² / 18 AWG;
Strip length: 10 … 11 mm / 0.39 … 0.43 inch;
Numar poli: 3;
Numar total de conexiuni: 12;
Total number of potentials: 3;
Wiring type: Side-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;
Distanta intre pini: 12 mm / 0.472 inch;
Latime: 36 mm / 1.417 inch;
Inaltime de la fata: 22,3 mm / 0.878 inch;
Adancime: 35 mm / 1.378 inch;
Tip montaj: Snap-in mounting foot;
Marking: N-PE-L1;

Culoare: black;
Fire load: 0,388; MJ
Greutate: 21,2; g
Tip ambalare: bag;
Tara de origine: DE;
GTIN: 4044918510509;
Customs tariff number: 85369010000;
Pret: 14,84 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/4-conductor-chassis-mount-terminal-strip-3-pole-n-pe-l1-with-ground-contact-4-mm2-4-00-mm2-black-141982