



**WAGO PCB TERMINAL BLOCK; 16 MM<sup>2</sup>; PIN SPACING 20 MM; 2-POLE; CAGE CLAMP®; COMMONING OPTION; 16,00 MM; GRAY**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 1000; V  
Tensiune nominala de supratensiune (III/3): 12; kV  
Tensiune nominala (III/2): 1000; V  
Tensiune nominala de supratensiune (III/2): 12; kV  
Tensiune nominala (II/2): 1000; V  
Tensiune nominala de supratensiune (II/2): 12; kV  
Curent nominal: 76; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Tensiune nominala UL (Use Group B): 600; V  
Curent nominal UL (Use Group B): 65; A  
Tensiune nominala UL (Use Group C): 600; V  
Curent nominal UL (Use Group C): 65; A  
Certificari: UL 1059;  
Tensiune nominala CSA (Use Group B): 600; V  
Curent nominal CSA (Use Group B): 65; A  
Tensiune nominala CSA (Use Group C): 600; V  
Curent nominal CSA (Use Group C): 65; A  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Solid conductor: 0,2 ... 16 mm<sup>2</sup> / 24 ... 6 AWG;  
Fine-stranded conductor: 0,2 ... 16 mm<sup>2</sup> / 24 ... 6 AWG;  
Fine-stranded conductor; with insulated ferrule: 0,25 ... 10 mm<sup>2</sup>;  
Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 10 mm<sup>2</sup>;  
Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;  
Conductor connection direction to PCB: 45; °

Numar poli: 2;  
Numar total de conexiuni: 2;  
Total number of potentials: 2;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Number of jumper slots: 1;  
Distanta intre pini: 20 mm / 0.787 inch;  
Latime: 41 mm / 1.614 inch;  
Inaltime: 33,5 mm / 1.319 inch;  
Inaltime de la fata: 27 mm / 1.063 inch;  
Adancime: 33,4 mm / 1.315 inch;  
Lungimea pinului de contact: 6,5; mm  
Solder pin dimensions: 1,2 x 1,6 mm;  
Diametrul de gaurire cu toleranta: 2,2 (+0,1) mm;  
Tip montaj: Mounting flange;  
Tip montaj: Panel mounting;  
PCB contact: THT;  
Solder pin arrangement: over the entire terminal strip (in-line);  
Number of solder pins per potential: 4;  
Culoare: gray;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Fire load: 0,472; MJ  
Greutate: 25,2; g  
Temperatura lucru: -60 ... +105 °C;  
Product Group: 4 (Printed Circuit);  
Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4044918303057;  
Customs tariff number: 85369010000;  
Pret: 18,01 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/pcb-terminal-block-16-mm2-pin-spacing-20-mm-2-pole-cage-clamp-commoning-option-16-00-mm2-gray-142043>