www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO TAP-OFF MODULE; FOR FLAT CABLE; 5 X 2.5 MM² + 2 X 1.5 MM²; 5-POLE; COD. A; WITH CABLE CONNECTION ON THE OUTPUT SIDE; BLACK

Note on Contact Resistance: approx. 1 m? of contact resistance approx. 0.25 m? contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 400; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 25; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: IDC;
Tip actionare: Operating tool;
Numar poli: 5;
Total number of potentials: 5;
Latime: 50 mm / 1.969 inch;
Inaltime: 46,5 mm / 1.831 inch;
Adancime: 79 mm / 3.11 inch;
Coding: A;
Mating force of a plug-in connection: approx. 30 … 70 N (depending on pole number);
Retention force of a plug-in connection: When locked: > 80 N;
Unmating force of a plug-in connection: when unlocked: approx. 15 … 20 N;
Number of mating cycles: ?200, without resistive load100, with resistive load IN = 25 A, tested (4 mm²/12 AWG);
Marking: N ? L1 L2 L3;
Protection type: IP20;
Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;
Potential marking: N ? L1 L2 L3;
Application: General mains applications;

Suitable: for flat cable 5 x 2.5 mm², 5 x 4 mm², 5 x 2.5 mm² + 2 x 1.5 mm²;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Culoare: black;
Material izolator: Polyamide 66 (PA 66);
Contact material: Copper or copper alloy (surface-treated);
Fire load: 1,772; MJ
Greutate: 76,4; g
Processing temperature: -5 … +40 °C;
Continuous operating temperature: -35 … +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free) PVC flat cable for temperatures –15 °C to ? 70 °C (including halogen-free) Insulating parts for temperatures ? 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454062002;
Customs tariff number: 85366990990;
Pret: 117,72 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/tap-off-module-for-flat-cable-5-x-2-5-mm2-2-x-1-5-mm2-5-pole-cod-a-with-cable-connection-on-the-output-side-black-142071