



WAGO PCB TERMINAL BLOCK; 6 MM²; PIN SPACING 12.5 MM; 9-POLE; CAGE CLAMP®; COMMONING OPTION; 6,00 MM²; GRAY

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 1000; V
Tensiune nominala de supratensiune (III/3): 8; kV
Tensiune nominala (III/2): 1000; V
Tensiune nominala de supratensiune (III/2): 8; kV
Tensiune nominala (II/2): 1000; V
Tensiune nominala de supratensiune (II/2): 8; kV
Curent nominal: 41; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 600; V
Curent nominal UL (Use Group B): 30; A
Tensiune nominala UL (Use Group C): 600; V
Curent nominal UL (Use Group C): 30; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 600; V
Curent nominal CSA (Use Group B): 30; A
Tensiune nominala CSA (Use Group C): 600; V
Curent nominal CSA (Use Group C): 30; A
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Solid conductor: 0,2 ... 6 mm² / 24 ... 10 AWG;
Fine-stranded conductor: 0,2 ... 6 mm² / 24 ... 10 AWG;
Fine-stranded conductor; with insulated ferrule: 0,25 ... 4 mm²;
Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 4 mm²;
Strip length: 11 ... 12 mm / 0.43 ... 0.47 inch;
Conductor connection direction to PCB: 45; °

Numar poli: 9;
Numar total de conexiuni: 9;
Total number of potentials: 9;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 12,5 mm / 0.492 inch;
Latime: 109,1 mm / 4.295 inch;
Inaltime: 27,5 mm / 1.083 inch;
Inaltime de la fata: 23 mm / 0.906 inch;
Adancime: 29,1 mm / 1.146 inch;
Lungimea pinului de contact: 4,5; mm
Solder pin dimensions: 1 x 1,4 mm;
Diametrul de gaurire cu toleranta: 1,8 (+0,1) mm;
PCB contact: THT;
Solder pin arrangement: over the entire terminal strip (in-line);
Number of solder pins per potential: 2;
Culoare: gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 1,11; MJ
Greutate: 57,9; g
Temperatura lucru: -60 ... +105 °C;
Product Group: 4 (Printed Circuit);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4045454625542;
Customs tariff number: 85369010000;
Pret: 53,55 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/pcb-terminal-block-6-mm2-pin-spacing-12-5-mm-9-pole-cage-clamp-commoning-option-6-00-mm2-gray-142137>