



**WAGO 2-CONDUCTOR TERMINAL STRIP; WITH SNAP-IN MOUNTING FEET; FOR  
PLATE THICKNESS 0.6 - 1.2 MM; FIXING HOLE 3.5 MM Ø; ALSO FITS 210-154  
ALUMINUM RAIL OR WITH 209-123 MOUNTING CARRIER FOR DIN 35 RAIL; 3-  
POLE; 2,50 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 24; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 14 AWG;  
Fine-stranded conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 14 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar poli: 3;  
Numar total de conexiuni: 6;  
Total number of potentials: 3;  
Numar nivele: 1;  
Wiring type: Side-entry wiring;  
Latime: 22.4 mm / 0.882 inch;  
Inaltime de la fata: 18 mm / 0.709 inch;  
Adancime: 28 mm / 1.102 inch;  
Module Latime: 6 mm / 0.236 inch;  
Design: horizontal;  
Tip montaj: Snap-in mounting foot;  
Marking level: Side marking;  
Culoare: gray;  
Fire load: 0,147; MJ

Greutate: 8,1; g  
Product Group: 9 (Std. Chassis Mt. Blocks);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918629263;  
Customs tariff number: 85369010000;  
Pret: 8,44 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-terminal-strip-with-snap-in-mounting-feet-for-plate-thickness-0-6-1-2-mm-fixing-hole-3-5-mm-oe-also-fits-210-154-aluminum-rail-or-with-209-123-mounting-carrier-for-din-35-rail-3-pole-2-50-mm2-gray-142373>