



WAGO SPACE-SAVING, 4-CONDUCTOR END TERMINAL BLOCK; WITHOUT PUSH-BUTTONS; WITHOUT PROTRUDING SNAP-IN MOUNTING FOOT; FOR TERMINAL STRIPS WITH SNAP-IN MOUNTING FEET; 2.5 MM²; CAGE CLAMP®; 2,50 MM²; GRAY

Tesiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,08 ... 2,5 mm² / 28 ... 14 AWG;

Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 14 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 4;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 10 mm / 0.394 inch;

Inaltime de la fata: 18 mm / 0.709 inch;

Adancime: 28 mm / 1.102 inch;

Design: horizontal type;

Tip montaj: Snap-in mounting foot;

Marking level: Side marking;

Culoare: gray;

Fire load: 0,051; MJ

Greutate: 3,6; g

Product Group: 9 (Std. Chassis Mt. Blocks);

Tip ambalare: BOX;

Tara de origine: CH;
GTIN: 4045454911201;
Customs tariff number: 85369010000;
Pret: 4,17 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/space-saving-4-conductor-end-terminal-block-without-push-buttons-without-protruding-snap-in-mounting-foot-for-terminal-strips-with-snap-in-mounting-feet-2-5-mm2-cage-clamp-2-50-mm2-gray-142432>