
www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO 4-CONDUCTOR DOUBLE DECK TERMINAL BLOCK; THROUGH/THROUGH TERMINAL BLOCK; N/N; WITHOUT MARKER CARRIER; SUITABLE FOR EX I APPLICATIONS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; PUSH-IN CAGE CLAMP®; 2,50 MM²; BLUE

Ratings per: IEC/EN 60947-7-1;
Tesiune nominala (III/3): 800; V
Tensiune nominala de supratensiune (III/3): 8; kV
Curent nominal: 24; A
Curent nominal 2: 28; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tensiune nominala UL (Use Group B): 600; V
Curent nominal UL (Use Group B): 20; A
Tensiune nominala UL (Use Group C): 600; V
Curent nominal UL (Use Group C): 20; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 600; V
Curent nominal CSA (Use Group B): 20; A
Tensiune nominala CSA (Use Group C): 600; V
Curent nominal CSA (Use Group C): 20; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Number of connection points (connection type): 4;
Tip actionare: Push-in; Open Tool Slot;
Connectable conductor materials: Copper;
Nominal cross-section: 2,5 mm²;
Solid conductor: 0,25 … 4 mm² / 22 … 12 AWG;
Solid conductor; push-in termination: 0,75 … 4 mm² / 18 … 12 AWG;
Fine-stranded conductor: 0,25 … 4 mm² / 22 … 12 AWG;
Fine-stranded conductor; with insulated ferrule: 1 … 2,5 mm² / 18 … 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 … 2,5 mm² / 18 … 12 AWG;
Strip length: 10 … 12 mm / 0.39 … 0.47 inch;
Number of connection points: 4;
Numar total de conexiuni: 8;
Total number of potentials: 2;
Numar nivele: 2;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;
Latime: 5,2 mm / 0.205 inch;
Inaltime from upper-edge of DIN-rail: 52,1 mm / 2.051 inch;
Adancime: 105,1 mm / 4.138 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Potential marking: N/N;
Marking level: Center/side marking;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,294; MJ
Greutate: 15,8; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4050821144991;
Customs tariff number: 85369010000;
Pret: 20,29 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/4-conductor-double-deck-terminal-block-through-through-terminal-block-n-n-without-marker-carrier-suitable-for-ex-i-applications-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-blue-142521