



**WAGO 3-CONDUCTOR THROUGH TERMINAL BLOCK; 6 MM<sup>2</sup>; WITH TEST OPTION;  
SAME PROFILE AS 3-CONDUCTOR DISCONNECT TERMINAL BLOCK; CENTER  
MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 6,00 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 41; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,2 ... 6 mm<sup>2</sup> / 24 ... 10 AWG;

Fine-stranded conductor: 0,2 ... 6 mm<sup>2</sup> / 24 ... 10 AWG;

Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;

Numar total de conexiuni: 3;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 8 mm / 0.315 inch;

Inaltime from upper-edge of DIN-rail: 32,5 mm / 1.28 inch;

Adancime: 85 mm / 3.346 inch;

Design: angled;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,313; MJ

Greutate: 19,8; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;

Tara de origine: CN;

GTIN: 4050821234548;

Customs tariff number: 85369010000;

Pret: 15,26 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/3-conductor-through-terminal-block-6-mm2-with-test-option-same-profile-as-3-conductor-disconnect-terminal-block-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-6-00-mm2-gray-142732>