



**WAGO 4-CONDUCTOR SENSOR SUPPLY TERMINAL BLOCK; WITH GROUND CONTACT; WITH END PLATE; WITH COLORED CONDUCTOR ENTRIES; 2.5 MM<sup>2</sup>; CAGE CLAMP®; 2,50 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 20; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper; Aluminum;

Solid conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 4;

Total number of potentials: 3;

Numar nivele: 4;

Wiring type: Front-entry wiring;

Note (conductor cross-section): 12 AWG: THHN, THWN;

Latime: 6 mm / 0.236 inch;

Inaltime from upper-edge of DIN-rail: 63,5 mm / 2.5 inch;

Adancime: 90,5 mm / 3.563 inch;

Design: angled;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,331; MJ

Greutate: 17,3; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4045454093891;

Customs tariff number: 85369010000;

Pret: 36,88 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-sensor-supply-terminal-block-with-ground-contact-with-end-plate-with-colored-conductor-entries-2-5-mm2-cage-clamp-2-50-mm2-gray-142795>