



WAGO THT MALE HEADER; 1.0 MM Ø SOLDER PIN; STRAIGHT; PIN SPACING 3.5 MM; 10-POLE; LIGHT GRAY

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 160; V
Tensiune nominala de supratensiune (III/3): 2,5; kV
Tensiune nominala (III/2): 160; V
Tensiune nominala de supratensiune (III/2): 2,5; kV
Tensiune nominala (II/2): 320; V
Tensiune nominala de supratensiune (II/2): 2,5; kV
Curent nominal: 10; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 10; A
Tensiune nominala UL (Use Group D): 300; V
Curent nominal UL (Use Group D): 10; A
Certificari: UL 1059;
Numar poli: 10;
Total number of potentials: 10;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 3,5 mm / 0.138 inch;
Latime: 37 mm / 1.457 inch;
Inaltime: 21,1 mm / 0.831 inch;
Inaltime de la fata: 17,5 mm / 0.689 inch;
Adancime: 12,4 mm / 0.488 inch;
Lungimea pinului de contact: 3,6; mm
Diametrul pinului de contact: 1; mm
Diametrul de gaurire cu toleranta: 1,2 (+0,1) mm;

Tip contact (pluggable connector): Conector tata/fisa;

Connector (connection type): for PCB;

Mismating protection: No;

Mating direction to the PCB: 90; °

Locking of plug-in connection: Locking latch;

PCB contact: THT;

Culoare: light gray;

Material group: I;

Material izolator: Polyphthalamide (PPA GF);

Flammability class per UL94: V0;

Contact material: Cupru electrolitic(ECu);

Contact plating: tin-plated;

Fire load: 0,064; MJ

Greutate: 3,3; g

Temperatura lucru: -60 ... +100 °C;

Product Group: 26 (picoMAX);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4050821161059;

Customs tariff number: 85366990990;

Pret: 11,33 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tht-male-header-1-0-mm-oe-solder-pin-straight-pin-spacing-3-5-mm-10-pole-light-gray-142975>