



**WAGO 3-CONDUCTOR ACTUATOR SUPPLY TERMINAL BLOCK; LED (YELLOW);
FOR PNP-(HIGH-SIDE) SWITCHING ACTUATORS; WITH GROUND CONTACT; 1
MM²; PUSH-IN CAGE CLAMP®; 1,00 MM²; GRAY**

Voltage type 1: DC;

Tensiune nominala: 24; V

Ratings per: IEC/EN 60947-7-1;

Curent nominal: 13,5; A

Tensiune nominala UL (Use Group C): 24; V

Curent nominal UL (Use Group C): 15; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group C): 24; V

Curent nominal CSA (Use Group C): 10; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 1 mm²;

Solid conductor: 0,14 ... 1,5 mm² / 24 ... 16 AWG;

Solid conductor; push-in termination: 0,5 ... 1,5 mm² / 20 ... 16 AWG;

Fine-stranded conductor: 0,14 ... 1,5 mm² / 24 ... 16 AWG;

Fine-stranded conductor; with insulated ferrule: 0,5 ... 0,75 mm² / 20 ... 18 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0,5 ... 0,75 mm² / 20 ... 18 AWG;

Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;

Numar total de conexiuni: 8;

Total number of potentials: 4;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Latime: 7 mm / 0.276 inch;
Inaltime from upper-edge of DIN-rail: 52,4 mm / 2.063 inch;
Adancime: 81,1 mm / 3.193 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Greutate: 19,3; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143452830;
Customs tariff number: 85369010000;
Pret: 82,40 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/3-conductor-actuator-supply-terminal-block-led-yellow-for-pnp-high-side-switching-actuators-with-ground-contact-1-mm2-push-in-cage-clamp-1-00-mm2-gray-142995>