



**WAGO SUPPLY MODULE; FOR FLAT CABLE; 5 X 2.5 MM<sup>2</sup> + 2 X 1.5 MM<sup>2</sup>; 2-POLE;**  
**GRAY**

Note on Contact Resistance: approx. 1 m<sup>2</sup> of contact resistance approx. 0.25 m<sup>2</sup> contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tesiune nominala (III/3): 50; V

Tensiune nominala de supratensiune (III/3): 0,8; kV

Curent nominal: 3; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Screw-type connection;

Tip actionare: Operating tool;

Conductor diameter: 0,8 mm;

Strip length: 5 ... 6 mm / 0.2 ... 0.24 inch;

Numar poli: 2;

Tehnologie conexiune 2: IDC;

Latime: 41 mm / 1.614 inch;

Inaltime: 35,5 mm / 1.398 inch;

Adancime: 21 mm / 0.827 inch;

Technologie: KNX;

Mating force of a plug-in connection: approx. 30 ... 70 N (depending on pole number);

Retention force of a plug-in connection: When locked: > 80 N;

Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N;

Number of mating cycles: ?200;

Protection type: IP20;

Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;

Application: KNX;

Suitable: for flat cable 5 x 2.5 mm<sup>2</sup> + 2 x 1.5 mm<sup>2</sup>;

Mismating protection: Yes;  
Locking of plug-in connection: locking lever;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire class per EN 50575: Eca;  
Contact material: Copper or copper alloy (surface-treated);  
Greutate: 26; g  
Processing temperature: -5 ... +40 °C;  
Continuous operating temperature: -35 ... +85 °C;  
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)  
PVC flat cable for temperatures -15 °C to ? 70 °C (including halogen-free) Insulating parts for temperatures ? 105 °C;  
Product Group: 20 (WINSTA);  
Tip ambalare: BOX;  
Tara de origine: CH;  
GTIN: 4045454267285;  
Customs tariff number: 85369010000;  
Pret: 101,58 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/supply-module-for-flat-cable-5-x-2-5-mm2-2-x-1-5-mm2-2-pole-gray-143077>