www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO SUPPLY MODULE; FOR FLAT CABLE; 5 X 2.5 MM² + 2 X 1.5 MM²; 2-POLE; GRAY

Note on Contact Resistance: approx. 1 m? of contact resistance approx. 0.25 m? contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 50; V
Tensiune nominala de supratensiune (III/3): 0,8; kV
Curent nominal: 3; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: Screw-type connection;
Tip actionare: Operating tool;
Conductor diameter: 0,8 mm;
Strip length: 5 … 6 mm / 0.2 … 0.24 inch;
Numar poli: 2;
Tehnologie conexiune 2: IDC;
Latime: 41 mm / 1.614 inch;
Inaltime: 35,5 mm / 1.398 inch;
Adancime: 21 mm / 0.827 inch;
Technologie: KNX;
Mating force of a plug-in connection: approx. 30 … 70 N (depending on pole number);
Retention force of a plug-in connection: When locked: > 80 N;
Unmating force of a plug-in connection: when unlocked: approx. 15 … 20 N;
Number of mating cycles: ?200;
Protection type: IP20;
Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;
Application: KNX;
Suitable: for flat cable 5 x 2.5 mm² + 2 x 1.5 mm²;

Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Eca;
Contact material: Copper or copper alloy (surface-treated);
Greutate: 26; g
Processing temperature: -5 … +40 °C;
Continuous operating temperature: -35 … +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free) PVC flat cable for temperatures –15 °C to ? 70 °C (including halogen-free) Insulating parts for temperatures ? 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4045454267285;
Customs tariff number: 85369010000;
Pret: 102,35 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/supply-module-for-flat-cable-5-x-2-5-mm2-2-x-1-5-mm2-2-pole-gray-143077