
www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO GROUND CONDUCTOR DISCONNECT TERMINAL BLOCK; WITH TEST OPTION; WITH ORANGE DISCONNECT LINK; 230 V; 6 MM²; PUSH-IN CAGE CLAMP®; 6,00 MM²; GRAY

Operation status indicator: 230 V;
Certificari: UL 1059;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-in; Operating tool;
Connectable conductor materials: Copper;
Nominal cross-section: 6 mm²;
Solid conductor: 0,5 … 10 mm² / 20 … 8 AWG;
Solid conductor; push-in termination: 2,5 … 10 mm² / 14 … 8 AWG;
Fine-stranded conductor: 0,5 … 10 mm² / 20 … 8 AWG;
Fine-stranded conductor; with insulated ferrule: 2,5 … 6 mm² / 16 … 10 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 2,5 … 6 mm² / 16 … 10 AWG;
Strip length: 13 … 15 mm / 0.51 … 0.59 inch;
Numar total de conexiuni: 4;
Total number of potentials: 2;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;
Number of jumper slots: 1;
Latime: 15 mm / 0.591 inch;
Inaltime from upper-edge of DIN-rail: 36,8 mm / 1.449 inch;
Adancime: 96,3 mm / 3.791 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;

Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Greutate: 40,6; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454789886;
Customs tariff number: 85365080900;
Pret: 197,69 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/ground-conductor-disconnect-terminal-block-with-test-option-with-orange-disconnect-link-230-v-6-mm2-push-in-cage-clamp-6-00-mm2-gray-143125