

WAGO 2-CONDUCTOR POWER DISTRIBUTION DISCONNECT TERMINAL BLOCK; 4 MM²; CAGE CLAMP®; 4,00 MM²; GRAY

Tesiune nominala (III/3): 400; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 32; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Open Tool Slot;
Connectable conductor materials: Copper; Aluminum;
Solid conductor: 0,08 … 4 mm² / 28 … 12 AWG;
Fine-stranded conductor: 0,08 … 4 mm² / 28 … 12 AWG;
Strip length: 9 … 10 mm / 0.35 … 0.39 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Latime: 6 mm / 0.236 inch;
Inaltime from upper-edge of DIN-rail: 43,5 mm / 1.713 inch;
Adancime: 77 mm / 3.031 inch;
Design: angled;
Tip montaj: DIN-35 rail;
Marking level: Center marking;
Culoare: gray;
Greutate: 17,9; g
Product Group: 17 (TOP JOB installation terminal blocks);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4044918808101;

Customs tariff number: 85365080900;
Pret: 18,23 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/2-conductor-power-distribution-disconnect-terminal-block-4-mm2-cage-clamp-4-00-mm2-gray-143181