



WAGO THROUGH-BOARD SMD PCB TERMINAL BLOCK; PIN SPACING 3 MM; 1-POLE; PUSH WIRE®; IN TAPE-AND-REEL PACKAGING; WITHOUT HOUSING; 0,75 MM²

Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 200; V
Tensiune nominala de supratensiune (III/3): 4; kV
Tesiune nominala (II/2): 500; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 9; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Tehnologie conexiune: PUSH WIRE®;
Tip actionare: Push-in;
Solid conductor: 0,34 ... 0,75 mm² / 20 ... 18 AWG;
Strip length: 3,7 mm / 0.15 inch;
Conductor connection direction to PCB: 90; °
Numar poli: 1;
Numar total de conexiuni: 1;
Total number of potentials: 1;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Latime: 3 mm / 0.118 inch;
Inaltime: 3,9 mm / 0.154 inch;
Adancime: 17,5 mm / 0.689 inch;
Reel diameter of tape-and-reel packaging: 330; mm
Tape Latime: 24; mm
PCB contact: SMD;
Material izolator: Polyamide 66 (PA 66);

Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Greutate: 0,2; g
Temperatura lucru: -60 ... +105 °C;
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4055143607636;
Customs tariff number: 85369010000;
Pret: 1,72 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/through-board-smd-pcb-terminal-block-pin-spacing-3-mm-1-pole-push-wire-in-tape-and-reel-packaging-without-housing-0-75-mm2-143250>