



**WAGO 4-CONDUCTOR TERMINAL BLOCK; SUITABLE FOR EX I APPLICATIONS;
WITHOUT PUSH-BUTTONS; WITH SNAP-IN MOUNTING FOOT; FOR PLATE
THICKNESS 0.6 - 1.2 MM; FIXING HOLE 3.5 MM Ø; 2.5 MM²; CAGE CLAMP®; 2,50
MM²; BLUE**

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 2.5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0.08 ... 2.5 mm² / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 4;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): 12 AWG: THHN, THWN;

Latime: 10 mm / 0.394 inch;

Inaltime de la fata: 22.1 mm / 0.87 inch;

Adancime: 32 mm / 1.26 inch;

Design: horizontal;

Tip montaj: Snap-in mounting foot;

Marking level: Center marking;

Culoare: blue;

Fire load: 0,115; MJ

Greutate: 6,4; g

Product Group: 9 (Std. Chassis Mt. Blocks);
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4044918414685;
Customs tariff number: 85369010000;
Pret: 6,98 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-terminal-block-suitable-for-ex-i-applications-without-push-buttons-with-snap-in-mounting-foot-for-plate-thickness-0-6-1-2-mm-fixing-hole-3-5-mm-oe-2-5-mm2-cage-clamp-2-50-mm2-blue-143344>