



**WAGO TAP-OFF MODULE; 5 X 4 MM<sup>2</sup>; WITH SPRING CLAMP CONNECTION;  
SCREW CONNECT. TO CABLE 5 X 10 MM<sup>2</sup>; TRANSPARENT**

Note on Contact Resistance: approx. 1 m<sup>2</sup> of contact resistance approx. 0.25 m<sup>2</sup> contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 690; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Numar poli: 5;

Numar total de conexiuni: 5;

Total number of potentials: 5;

Latime: 51 mm / 2.008 inch;

Inaltime: 48 mm / 1.89 inch;

Adancime: 110 mm / 4.331 inch;

Mating force of a plug-in connection: approx. 30 ... 70 N (depending on pole number);

Retention force of a plug-in connection: When locked: > 80 N;

Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N;

Number of mating cycles: ?200, without resistive load 100, with resistive load IN = 25 A, tested (4 mm<sup>2</sup>/AWG 12);

Protection type: IP20;

Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;

Suitable: for flat cable 5 x 10 mm<sup>2</sup>;

Mismating protection: Yes;

Locking of plug-in connection: locking lever;

Culoare: transparent;  
Material izolator: Polyamide 66 (PA 66);  
Contact material: Copper or copper alloy (surface-treated);  
Fire load: 2,232; MJ  
Greutate: 171,8; g  
Processing temperature: -5 ... +40 °C;  
Continuous operating temperature: -35 ... +85 °C;  
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)  
PVC flat cable for temperatures -15 °C to ? 70 °C (including halogen-free) Insulating parts for temperatures ? 105 °C;  
Product Group: 20 (WINSTA);  
Tip ambalare: BOX;  
Tara de origine: CH;  
GTIN: 4045454006266;  
Customs tariff number: 85369010000;  
Pret: 197,46 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tap-off-module-5-x-4-mm2-with-spring-clamp-connection-screw-connect-to-cable-5-x-10-mm2-transparent-143453>