
www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO 5-WAY DISTRIBUTION CONNECTOR; 2-POLE; COD. I; 1 INPUT; 5 OUTPUTS; BLUE

Note on Contact Resistance: approx. 1 m? of contact resistance approx. 0.25 m? contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Curent nominal: 16; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tensiune nominala UL 1977: 600; V
Curent nominal UL 1977: 14; A
Numar poli: 2;
Total number of potentials: 2;
Distanta intre pini: 4,4 mm / 0.173 inch;
Latime: 12 mm / 0.472 inch;
Inaltime: 43,6 mm / 1.717 inch;
Adancime: 63,5 mm / 2.5 inch;
Technologie: DALI;
Coding: I;
Mating force of a plug-in connection: approx. 20 … 70 N (depending on pole number);
Retention force of a plug-in connection: When locked: > 80 N;
Unmating force of a plug-in connection: when unlocked: approx. 20 … 70 N (depending on pole number);
Number of mating cycles: ?200, without resistive load100, with resistive load IN = 16 A, tested (1.5mm²/AWG 16);
Distributor type: Distribution connector (5-way);
Marking: + -;
Protection type: IP20;
Note on protection type: IP40 when mated;

Potential marking: + -;
Application: Lighting management;
Tip contact (pluggable connector): Socket/plug;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: yes;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Contact material: Copper or copper alloy (surface-treated);
Greutate: 17,9; g
Processing temperature: -5 … +40 °C;
Continuous operating temperature: -35 … +85 °C;
Note on continuous operating temperature: Insulating parts for temperatures ? 105 °C;
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143609043;
Customs tariff number: 85366990990;
Pret: 50,78 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/5-way-distribution-connector-2-pole-cod-i-1-input-5-outputs-blue-143575