www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO QUADRUPLE-DECK RAIL-MOUNTED TERMINAL BLOCK; RAIL-MOUNTED TERMINAL BLOCK FOR ELECTRIC MOTOR WIRING; L1 - L2 - L3; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 4 MM²; CAGE CLAMP®; 4,00 MM²; GRAY

Ratings per: IEC/EN 60947-7-1;
Tesiune nominala (III/3): 400; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 20; A
Curent nominal 2: 25; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper; Aluminum;
Nominal cross-section: 2,5 mm²;
Solid conductor: 0,08 … 4 mm² / 28 … 12 AWG;
Fine-stranded conductor: 0,08 … 4 mm² / 28 … 12 AWG;
Strip length: 8 … 9 mm / 0.31 … 0.35 inch;
Numar total de conexiuni: 6;
Total number of potentials: 3;
Numar nivele: 4;
Wiring type: Front-entry wiring;
Latime: 6 mm / 0.236 inch;
Inaltime from upper-edge of DIN-rail: 62,5 mm / 2.461 inch;
Adancime: 100 mm / 3.937 inch;
Design: angled;
Tip montaj: DIN-35 rail;
Potential marking: L1 - L2 - L3;
Marking level: Center/side marking;
Culoare: gray;

Material izolator: Polyamide 66 (PA 66);
Fire load: 0,359; MJ
Greutate: 19,8; g
Product Group: 1 (Rail Mounted Terminal Blocks);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918787611;
Customs tariff number: 85369010000;
Pret: 22,94 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/quadruple-deck-rail-mounted-terminal-block-rail-mounted-terminal-block-for-electric-motor-wiring-l1-l2-l3-for-din-rail-35-x-15-and-35-x-7-5-4-mm2-cage-clamp-4-00-mm2-gray-143739