



**WAGO QUADRUPLE-DECK RAIL-MOUNTED TERMINAL BLOCK; RAIL-MOUNTED  
TERMINAL BLOCK FOR ELECTRIC MOTOR WIRING; L1 - L2 - L3; FOR DIN-RAIL 35  
X 15 AND 35 X 7.5; 4 MM<sup>2</sup>; CAGE CLAMP<sup>®</sup>; 4,00 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 20; A

Curent nominal 2: 25; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP<sup>®</sup>;

Tip actionare: Operating tool;

Connectable conductor materials: Copper; Aluminum;

Nominal cross-section: 2,5 mm<sup>2</sup>;

Solid conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 6;

Total number of potentials: 3;

Numar nivele: 4;

Wiring type: Front-entry wiring;

Latime: 6 mm / 0.236 inch;

Inaltime from upper-edge of DIN-rail: 62,5 mm / 2.461 inch;

Adancime: 100 mm / 3.937 inch;

Design: angled;

Tip montaj: DIN-35 rail;

Potential marking: L1 - L2 - L3;

Marking level: Center/side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,359; MJ  
Greutate: 19,8; g  
Product Group: 1 (Rail Mounted Terminal Blocks);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918787611;  
Customs tariff number: 85369010000;  
Pret: 22,73 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/quadruple-deck-rail-mounted-terminal-block-rail-mounted-terminal-block-for-electric-motor-wiring-11-12-13-for-din-rail-35-x-15-and-35-x-7-5-4-mm2-cage-clamp-4-00-mm2-gray-143739>