



WAGO 3-CONDUCTOR SENSOR SUPPLY TERMINAL BLOCK; FOR PNP (POSITIVE) SWITCHING SENSORS; POWER SUPPLY FROM CONTROL PANEL SIDE; WITH COLORED CONDUCTOR ENTRIES; 2,5 MM²; PUSH-IN CAGE CLAMP®; 2,50 MM²; ORANGE

Ratings per: IEC/EN 60947-7-1;
Tensiune nominala (III/3): 250; V
Curent nominal: 28; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tensiune nominala UL (Use Group C): 300; V
Curent nominal UL (Use Group C): 20; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group C): 300; V
Curent nominal CSA (Use Group C): 20; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-in; Open Tool Slot;
Connectable conductor materials: Copper;
Nominal cross-section: 1 mm²;
Solid conductor: 0,14 ... 1,5 mm² / 24 ... 16 AWG;
Solid conductor; push-in termination: 0,5 ... 1,5 mm² / 20 ... 16 AWG;
Fine-stranded conductor: 0,14 ... 1,5 mm² / 24 ... 16 AWG;
Fine-stranded conductor; with insulated ferrule: 0,5 ... 0,75 mm² / 20 ... 18 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 0,5 ... 0,75 mm² / 20 ... 18 AWG;
Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;
Solid conductor 2: 0,25 ... 4 mm² / 22 ... 12 AWG;
Solid conductor, push-in termination 2: 0,25 ... 4 mm² / 22 ... 12 AWG;
Fine-stranded conductor 2: 0,25 ... 4 mm² / 22 ... 12 AWG;
Numar total de conexiuni: 8;
Total number of potentials: 2;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 7 mm / 0.276 inch;

Inaltime from upper-edge of DIN-rail: 49,4 mm / 1.945 inch;

Adancime: 81,1 mm / 3.193 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;

Culoare: orange;

Material izolator: Polyamide 66 (PA 66);

Greutate: 15,8; g

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4055143497121;

Customs tariff number: 85369010000;

Pret: 34,25 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/3-conductor-sensor-supply-terminal-block-for-pnp-positive-switching-sensors-power-supply-from-control-panel-side-with-colored-conductor-entries-2-5-mm2-push-in-cage-clamp-2-50-mm2-orange-143810>