
www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO 3-CONDUCTOR SENSOR SUPPLY TERMINAL BLOCK; FOR PNP (POSITIVE) SWITCHING SENSORS; POWER SUPPLY FROM CONTROL PANEL SIDE; WITH COLORED CONDUCTOR ENTRIES; 2.5 MM²; PUSH-IN CAGE CLAMP®; 2,50 MM²; ORANGE

Ratings per: IEC/EN 60947-7-1;
Tesiune nominala (III/3): 250; V
Curent nominal: 28; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tensiune nominala UL (Use Group C): 300; V
Curent nominal UL (Use Group C): 20; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group C): 300; V
Curent nominal CSA (Use Group C): 20; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-in; Open Tool Slot;
Connectable conductor materials: Copper;
Nominal cross-section: 1 mm²;
Solid conductor: 0,14 … 1,5 mm² / 24 … 16 AWG;
Solid conductor; push-in termination: 0,5 … 1,5 mm² / 20 … 16 AWG;
Fine-stranded conductor: 0,14 … 1,5 mm² / 24 … 16 AWG;
Fine-stranded conductor; with insulated ferrule: 0,5 … 0,75 mm² / 20 … 18 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 0,5 … 0,75 mm² / 20 … 18 AWG;
Strip length: 9 … 11 mm / 0.35 … 0.43 inch;
Solid conductor 2: 0,25 … 4 mm² / 22 … 12 AWG;
Solid conductor, push-in termination 2: 0,25 … 4 mm² / 22 … 12 AWG;
Fine-stranded conductor 2: 0,25 … 4 mm² / 22 … 12 AWG;
Numar total de conexiuni: 8;
Total number of potentials: 2;

Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;
Latime: 7 mm / 0.276 inch;
Inaltime from upper-edge of DIN-rail: 49,4 mm / 1.945 inch;
Adancime: 81,1 mm / 3.193 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: orange;
Material izolator: Polyamide 66 (PA 66);
Greutate: 15,8; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143497121;
Customs tariff number: 85369010000;
Pret: 34,57 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/3-conductor-sensor-supply-terminal-block-for-pnp-positive-switching-sensors-power-supply-from-control-panel-side-with-colored-conductor-entries-2-5-mm2-push-in-cage-clamp-2-50-mm2-orange-143810