www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 95 MM²; SUITABLE FOR EX E II APPLICATIONS; LATERAL MARKER SLOTS; ONLY FOR DIN 35 X 15 RAIL; POWER CAGE CLAMP; 95,00 MM²; LIGHT GRAY

Ratings per: IEC/EN 60947-7-1;
Tensiune nominala EN (Ex e II): 880; V
Curent nominal (Ex e II) with jumper: 211; A
Tehnologie conexiune: POWER CAGE CLAMP;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 25 … 95 mm² / 4 … 4/0 AWG;
Stranded conductor: 25 … 95 mm² / 4 … 4/0 AWG;
Fine-stranded conductor: 25 … 95 mm² / 4 … 4/0 AWG;
Strip length: 35 mm / 1.38 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Side-entry wiring;
Latime: 25 mm / 0.984 inch;
Inaltime from upper-edge of DIN-rail: 101 mm / 3.976 inch;
Adancime: 107 mm / 4.213 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Marking level: Side marking;
Culoare: light gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 3,488; MJ
Greutate: 263,5; g
Tip ambalare: BOX;

Tara de origine: PL;
GTIN: 4055143254311;
Customs tariff number: 85369010000;
Pret: 169,24 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/2-conductor-through-terminal-block-95-mm2-suitable-for-ex-e-ii-applications-lateral-marker-slots-only-for-din-35-x-15-rail-power-cage-clamp-95-00-mm2-light-gray-143816