



**WAGO COMPACT SPLICING CONNECTOR; FOR ALL CONDUCTOR TYPES; FOR EX  
E APPLICATIONS; MAX. 4 MM<sup>2</sup>; 3-CONDUCTOR; WITH LEVERS; TRANSPARENT  
HOUSING; OPERATING TEMPERATURE (MAX.): 105 °C; 4,00 MM<sup>2</sup>; TRANSPARENT**

Ratings per: IEC/EN 60079-7;  
Tensiune nominala UL (Use Group C): 440; V  
Curent nominal UL (Use Group C): 20; A  
Certificari: UL 60079;  
Tensiune nominala EN (Ex e II): 440; V  
Curent nominal (Ex e II): 32; A  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Lever;  
Connectable conductor materials: Copper;  
Nominal cross-section: 4 mm<sup>2</sup>;  
Solid conductor: 0,2 ... 4 mm<sup>2</sup> / 24 ... 12 AWG;  
Stranded conductor: 0,2 ... 4 mm<sup>2</sup> / 24 ... 12 AWG;  
Fine-stranded conductor: 0,14 ... 4 mm<sup>2</sup> / 24 ... 12 AWG;  
Strip length: 11 mm / 0.43 inch;  
Numar total de conexiuni: 3;  
Total number of potentials: 1;  
Wiring type: Side-entry wiring;  
Latime: 18,7 mm / 0.736 inch;  
Inaltime: 8,3 mm / 0.327 inch;  
Adancime: 18,6 mm / 0.732 inch;  
Culoare: transparent;  
Flammability class per UL94: V2;  
Greutate: 2,7; g  
Continuous operating temperature: 105 °C;

Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4055143837347;  
Customs tariff number: 85369010000;

Pret: 4,09 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/compact-splicing-connector-for-all-conductor-types-for-ex-e-applications-max-4-mm2-3-conductor-with-levers-transparent-housing-operating-temperature-max-105-0c-4-00-mm2-transparent-143817>