



**WAGO 1-CONDUCTOR N-DISCONNECT TERMINAL BLOCK; 10 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®; 10,00 MM<sup>2</sup>; BLUE**

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 57; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 10 mm<sup>2</sup>;

Solid conductor: 0,5 ... 16 mm<sup>2</sup> / 20 ... 6 AWG;

Solid conductor; push-in termination: 4 ... 16 mm<sup>2</sup> / 14 ... 6 AWG;

Fine-stranded conductor: 0,5 ... 16 mm<sup>2</sup> / 20 ... 6 AWG;

Fine-stranded conductor; with insulated ferrule: 4 ... 10 mm<sup>2</sup> / 12 ... 8 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 4 ... 10 mm<sup>2</sup> / 12 ... 8 AWG;

Strip length: 17 ... 19 mm / 0.67 ... 0.75 inch;

Numar total de conexiuni: 1;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Number of jumper slots: 2;

Latime: 10 mm / 0.394 inch;

Inaltime from upper-edge of DIN-rail: 38,1 mm / 1.5 inch;

Adancime: 67,3 mm / 2.65 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;  
Culoare: blue;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 21,8; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4055143879699;  
Customs tariff number: 85365080900;  
Pret: 24,69 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/1-conductor-n-disconnect-terminal-block-10-mm2-push-in-cage-clamp-10-00-mm2-blue-143905>