www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO 1-CONDUCTOR N-DISCONNECT TERMINAL BLOCK; 10 MM²; PUSH-IN CAGE CLAMP®; 10,00 MM²; BLUE

Tesiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Curent nominal: 57; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-in; Open Tool Slot;
Connectable conductor materials: Copper;
Nominal cross-section: 10 mm²;
Solid conductor: 0,5 … 16 mm² / 20 … 6 AWG;
Solid conductor; push-in termination: 4 … 16 mm² / 14 … 6 AWG;
Fine-stranded conductor: 0,5 … 16 mm² / 20 … 6 AWG;
Fine-stranded conductor; with insulated ferrule: 4 … 10 mm² / 12 … 8 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 4 … 10 mm² / 12 … 8 AWG;
Strip length: 17 … 19 mm / 0.67 … 0.75 inch;
Numar total de conexiuni: 1;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;
Number of jumper slots: 2;
Latime: 10 mm / 0.394 inch;
Inaltime from upper-edge of DIN-rail: 38,1 mm / 1.5 inch;
Adancime: 67,3 mm / 2.65 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;

Marking level: Center/side marking;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Greutate: 21,8; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143879699;
Customs tariff number: 85365080900;
Pret: 24,92 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/1-conductor-n-disconnect-terminal-block-10-mm2-push-in-cage-clamp-10-00-mm2-blue-143905