



**WAGO THR MALE HEADER; 1.0 X 1.0 MM SOLDER PIN; ANGLED; 100%
PROTECTED AGAINST MISMATING; IN TAPE-AND-REEL PACKAGING; PIN
SPACING 3.5 MM; 4-POLE; BLACK**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 160; V

Tensiune nominala de supratensiune (III/3): 2,5; kV

Tensiune nominala (III/2): 160; V

Tensiune nominala de supratensiune (III/2): 2,5; kV

Tensiune nominala (II/2): 320; V

Tensiune nominala de supratensiune (II/2): 2,5; kV

Curent nominal: 10; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 10; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 10; A

Tensiune nominala CSA (Use Group D): 300; V

Curent nominal CSA (Use Group D): 10; A

Numar poli: 4;

Total number of potentials: 4;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 3,5 mm / 0.138 inch;

Latime: 16,4 mm / 0.646 inch;

Inaltime: 10,9 mm / 0.429 inch;

Inaltime de la fata: 8,5 mm / 0.335 inch;
Adancime: 10,3 mm / 0.406 inch;
Lungimea pinului de contact: 2,4; mm
Solder pin dimensions: 1 x 1 mm;
Diametru placat prin gaura (THR): 1,4 (+0,1) mm;
Reel diameter of tape-and-reel packaging: 330; mm
Tape Latime: 32; mm
Tip contact (pluggable connector): Conector tata/fisa;
Connector (connection type): for PCB;
Mismating protection: Yes;
Mating direction to the PCB: 0; °
PCB contact: THR;
Solder pin arrangement: over the entire male connector (in-line);
Number of solder pins per potential: 1;
Culoare: black;
Material group: I;
Material izolator: Polyphthalamide (PPA GF);
Flammability class per UL94: V0;
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,024; MJ
Greutate: 1,2; g
Temperatura lucru: -60 ... +100 °C;
Tip ambalare: bag;
Tara de origine: DE;
GTIN: 4044918937214;
Customs tariff number: 85366990990;
Pret: 8,15 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/thr-male-header-1-0-x-1-0-mm-solder-pin-angled-100-protected-against-mismating-in-tape-and-reel-packaging-pin-spacing-3-5-mm-4-pole-black-143985>