



**WAGO 2-CONDUCTOR TERMINAL STRIP; 8-POLE; WITHOUT PUSH-BUTTONS;
WITH SNAP-IN MOUNTING FEET; FOR PLATE THICKNESS 0.6 - 1.2 MM; FIXING
HOLE 3.5 MM Ø; 2.5 MM²; CAGE CLAMP®; 2,50 MM²; GRAY**

Tesiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 2.5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0.08 ... 2.5 mm² / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar poli: 8;

Numar total de conexiuni: 16;

Total number of potentials: 8;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): 12 AWG: THHN, THWN;

Latime: 55 mm / 2.165 inch;

Inaltime de la fata: 22.1 mm / 0.87 inch;

Adancime: 32 mm / 1.26 inch;

Module Latime: 6 mm / 0.236 inch;

Design: horizontal;

Tip montaj: Snap-in mounting foot;

Marking level: Center marking;

Culoare: gray;

Fire load: 0,66; MJ

Greutate: 32,7; g
Product Group: 9 (Std. Chassis Mt. Blocks);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918423670;
Customs tariff number: 85369010000;
Pret: 39,09 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-terminal-strip-8-pole-without-push-buttons-with-snap-in-mounting-feet-for-plate-thickness-0-6-1-2-mm-fixing-hole-3-5-mm-oe-2-5-mm2-cage-clamp-2-50-mm2-gray-144005>