



**WAGO 3-CONDUCTOR, DOUBLE-DECK TERMINAL BLOCK; GREEN-YELLOW  
CONDUCTOR ENTRY; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM<sup>2</sup>; CAGE CLAMP®;  
2,50 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;

Numar total de conexiuni: 6;

Total number of potentials: 2;

Numar nivele: 2;

Wiring type: Front-entry wiring;

Latime: 5 mm / 0.197 inch;

Inaltime from upper-edge of DIN-rail: 40 mm / 1.575 inch;

Adancime: 91 mm / 3.583 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Potential marking: PE/L;

Marking level: Side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,204; MJ

Greutate: 15,3; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4045454094515;  
Customs tariff number: 85369010000;  
Pret: 24,45 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/3-conductor-double-deck-terminal-block-green-yellow-conductor-entry-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-gray-144192>