



WAGO SOLDER PIN STRIP; 1.0 MM Ø SOLDER PIN; ANGLED; PIN SPACING 3.5 MM;
5-POLE; BLACK

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 160; V
Tensiune nominala de supratensiune (III/3): 2,5; kV
Tensiune nominala (III/2): 160; V
Tensiune nominala de supratensiune (III/2): 2,5; kV
Tensiune nominala (II/2): 320; V
Tensiune nominala de supratensiune (II/2): 2,5; kV
Curent nominal: 10; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Numar poli: 5;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 3.5 mm / 0.138 inch;
Latime: 19.2 mm / 0.756 inch;
Inaltime: 5.9 mm / 0.232 inch;
Inaltime de la fata: 3.5 mm / 0.138 inch;
Adancime: 10.2 mm / 0.402 inch;
Lungimea pinului de contact: 2,4; mm
Diametrul pinului de contact: 1; mm
Diametru placat prin gaura (THR): 1.2 (+0.1) mm;
Tip contact (pluggable connector): Conector tata/fisa;
Connector (connection type): for PCBs;
Mismating protection: No;
Mating direction to the PCB: 0; °
PCB contact: THR;

Culoare: black;
Material group: I;
Material izolator: Polyphthalamide (PPA GF);
Flammability class per UL94: V0;
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Greutate: 0,6; g
Temperatura lucru: -60 ... +100 °C;
Tip ambalare: bag;
Tara de origine: CN;
GTIN: 4055143935654;
Customs tariff number: 85369010000;
Pret: 4,41 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/solder-pin-strip-1-0-mm-oe-solder-pin-angled-pin-spacing-3-5-mm-5-pole-black-144448>