



**WAGO THR FEMALE HEADER; 0.4 X 0.9 MM SOLDER PIN; STRAIGHT; PIN SPACING  
3.5 MM; 6-POLE; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 160; V

Tensiune nominala de supratensiune (III/3): 2,5; kV

Tensiune nominala (III/2): 160; V

Tensiune nominala de supratensiune (III/2): 2,5; kV

Tensiune nominala (II/2): 320; V

Tensiune nominala de supratensiune (II/2): 2,5; kV

Curent nominal: 10; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 10; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Numar poli: 6;

Total number of potentials: 6;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 3,5 mm / 0.138 inch;

Latime: 21 mm / 0.827 inch;

Inaltime: 16,2 mm / 0.638 inch;

Inaltime de la fata: 13,8 mm / 0.543 inch;

Adancime: 11,6 mm / 0.457 inch;

Lungimea pinului de contact: 2,4; mm

Solder pin dimensions: 0,4 x 0,9 mm;

Diametru placat prin gaura (THR): 1,1 (+0,1) mm;

Tip contact (pluggable connector): Conector mama/priza;

Connector (connection type): for PCB;

Mismating protection: No;

Mating direction to the PCB: 90; °

PCB contact: THR;

Culoare: light gray;

Material group: I;

Material izolator: Polyphthalamide (PPA GF);

Flammability class per UL94: V0;

Contact material: Copper alloy;

Contact plating: tin-plated;

Fire load: 0,075; MJ

Greutate: 3,1; g

Temperatura lucru: -60 ... +100 °C;

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4050821395959;

Customs tariff number: 85366990990;

Pret: 22,12 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/thr-female-header-0-4-x-0-9-mm-solder-pin-straight-pin-spacing-3-5-mm-6-pole-light-gray-144558>