



**WAGO CLEMA RAPIDA PENTRU CONDUCTORI RIGIZI MAX. 2.5 MM<sup>2</sup>; 4-  
CONDUCTOR; TRANSPARENT -PORTOCALIU**

Ratings per: IEC/EN 60664-1;  
Tesiune nominala (II/2): 400; V  
Tensiune nominala de supratensiune (II/2): 4; kV  
Curent nominal: 24; A  
Legend (ratings): (II / 2) ? Overvoltage category II / Pollution degree 2;  
Tehnologie conexiune: PUSH WIRE®;  
Tip actionare: Push-in;  
Connectable conductor materials: Copper; Aluminum;  
Solid conductor: 0,75 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;  
Stranded conductor: 1,5 ... 2,5 mm<sup>2</sup> / 16 ... 12 AWG;  
Strip length: 12 mm / 0.47 inch;  
Numar total de conexiuni: 4;  
Total number of potentials: 1;  
Wiring type: Side-entry wiring;  
Latime: 13 mm / 0.512 inch;  
Inaltime: 13,1 mm / 0.516 inch;  
Adancime: 19,5 mm / 0.768 inch;  
Cover Culoare: orange;  
Flammability class per UL94: V2;  
Fire load: 0,056; MJ  
Greutate: 2,5; g  
Surrounding air temperature (operation): 60 °C;  
Product Group: 7 (Push Wire Conn.);  
Tip ambalare: BOX;  
Tara de origine: CN;

GTIN: 4044918397629;  
Customs tariff number: 85369010000;

Pret: 1,15 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/push-wire-connector-for-junction-boxes-for-solid-and-stranded-conductors-max-2-5-mm2-4-conductor-transparent-housing-orange-cover-surrounding-air-temperature-max-600c-2-50-mm2-144659>