



WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 95 MM²; LATERAL MARKER SLOTS; ONLY FOR DIN 35 X 15 RAIL; POWER CAGE CLAMP; 95,00 MM; GRAY

Voltage type 1: AC/DC;

Voltage type 2: DC;

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 1000; V

Tensiune nominala de supratensiune (III/3): 12; kV

Curent nominal: 232; A

Tensiune nominala (III/3) 2: 1500; V

Tensiune nominala de supratensiune (III/3) 2: 12; kV

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: POWER CAGE CLAMP;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 25 ... 95 mm² / 4 ... 4/0 AWG;

Stranded conductor: 25 ... 95 mm² / 4 ... 4/0 AWG;

Fine-stranded conductor: 25 ... 95 mm² / 4 ... 4/0 AWG;

Strip length: 35 mm / 1.38 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 25 mm / 0.984 inch;

Inaltime from upper-edge of DIN-rail: 101 mm / 3.976 inch;

Adancime: 107 mm / 4.213 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Side marking;

Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 3,564; MJ
Greutate: 264,3; g
Product Group: 1 (Rail Mounted Terminal Blocks);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4044918452564;
Customs tariff number: 85369010000;
Pret: 153,90 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-through-terminal-block-95-mm2-lateral-marker-slots-only-for-din-35-x-15-rail-power-cage-clamp-95-00-mm2-gray-144666>