www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES; FOR SOLID AND STRANDED CONDUCTORS; MAX. 6 MM²; 3-CONDUCTOR; TRANSPARENT HOUSING; RED COVER; SURROUNDING AIR TEMPERATURE: MAX 60°C; 6,00 MM²

Ratings per: IEC/EN 60664-1;
Tesiune nominala (II/2): 400; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 41; A
Legend (ratings): (II / 2) ? Overvoltage category II / Pollution degree 2;
Tehnologie conexiune: PUSH WIRE®;
Tip actionare: Push-in;
Connectable conductor materials: Copper; Aluminum;
Solid conductor: 2,5 … 6 mm² / 14 … 10 AWG;
Stranded conductor: 2,5 … 6 mm² / 14 … 10 AWG;
Strip length: 12 … 13 mm / 0.47 … 0.51 inch;
Numar total de conexiuni: 3;
Total number of potentials: 1;
Wiring type: Side-entry wiring;
Latime: 25,6 mm / 1.008 inch;
Inaltime: 14,2 mm / 0.559 inch;
Adancime: 20,1 mm / 0.791 inch;
Cover Culoare: red;
Flammability class per UL94: V2;
Fire load: 0,115; MJ
Greutate: 5,8; g
Surrounding air temperature (operation): 60 °C;
Continuous operating temperature: 105 °C;
Tip ambalare: BOX;
Tara de origine: CN;

GTIN: 4050821215141;
Customs tariff number: 85369010000;
Pret: 0,82 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/push-wire-connector-for-junction-boxes-for-solid-and-stranded-conductors-max-6-mm2-3-conductor-transparent-housing-red-cover-surrounding-air-temperature-max-600c-6-00-mm2-144675