



**WAGO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES; FOR SOLID CONDUCTORS; MAX. 4 MM<sup>2</sup>; 4-CONDUCTOR; BROWN CLEAR HOUSING; RED COVER; SURROUNDING AIR TEMPERATURE: MAX 60°C; 2,50 MM<sup>2</sup>**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (II/2): 400; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 32; A

Legend (ratings): (II / 2) ? Overvoltage category II / Pollution degree 2;

Tehnologie conexiune: PUSH WIRE®;

Tip actionare: Push-in;

Connectable conductor materials: Copper; Aluminum;

Strip length: 12 mm / 0.47 inch;

Numar total de conexiuni: 6;

Total number of potentials: 1;

Wiring type: Side-entry wiring;

Latime: 13 mm / 0.512 inch;

Inaltime: 13,1 mm / 0.516 inch;

Adancime: 19,5 mm / 0.768 inch;

Cover Culoare: red;

Flammability class per UL94: V2;

Greutate: 2,4; g

Surrounding air temperature (operation): 60 °C;

Continuous operating temperature: 105 °C;

Product Group: 7 (Push Wire Conn.);

Tip ambalare: BOX;

Tara de origine: CN;

GTIN: 4055143243681;

Customs tariff number: 85369010000;

Pret: 2,08 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/push-wire-connector-for-junction-boxes-for-solid-conductors-max-4-mm2-4-conductor-brown-clear-housing-red-cover-surrounding-air-temperature-max-600c-2-50-mm2-144678>