

WAGO MICRO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES; FOR SOLID CONDUCTORS; 0.8 MM Ø; 4-CONDUCTOR; LIGHT GRAY COVER; SURROUNDING AIR TEMPERATURE: MAX 60°C; YELLOW

Ratings per: EN 60664;
Tesiune nominala (II/2): 100; V
Tensiune nominala de supratensiune (II/2): 1,5; kV
Curent nominal: 6; A
Legend (ratings): (II / 2) ? Overvoltage category II / Pollution degree 2;
Tehnologie conexiune: PUSH WIRE®;
Tip actionare: Push-in;
Connectable conductor materials: Copper;
Conductor diameter: 0,6 … 0,8 mm;
Strip length: 5 … 6 mm / 0.2 … 0.24 inch;
Numar total de conexiuni: 4;
Total number of potentials: 1;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Wiring type: Side-entry wiring;
Latime: 10 mm / 0.394 inch;
Inaltime: 6,8 mm / 0.268 inch;
Adancime: 10 mm / 0.394 inch;
Culoare: yellow;
Fire load: 0,012; MJ
Greutate: 0,8; g
Surrounding air temperature (operation): 60 °C;
Continuous operating temperature: 105 °C;
Tip ambalare: BOX;

Tara de origine: DE;
GTIN: 4044918440813;
Customs tariff number: 85369010000;

Pret: 1,15 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/micro-push-wire-connector-for-junction-boxes-for-solid-conductors-0-8-mm-oe-4-conductor-light-gray-cover-surrounding-air-temperature-max-600c-yellow-144713