



**WAGO 1-CONDUCTOR FEMALE PLUG; ANGLED; 4 MM<sup>2</sup>; 4-POLE; 4,00 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 61984;  
Tensiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 32; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Nominal cross-section: 4 mm<sup>2</sup>;  
Solid conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar poli: 4;  
Numar total de conexiuni: 4;  
Total number of potentials: 4;  
Wiring type: Front-entry wiring;  
Latime: 50 mm / 1.969 inch;  
Inaltime: 37,1 mm / 1.461 inch;  
Adancime: 26,5 mm / 1.043 inch;  
Module Latime: 5 mm / 0.197 inch;  
Marking level: Side marking;  
Tip contact (pluggable connector): Conector mama/priza;  
Connector (connection type): for conductor;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,175; MJ  
Greutate: 9,8; g

Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918547543;  
Customs tariff number: 85366990990;  
Pret: 20,03 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-female-plug-angled-4-mm2-4-pole-4-00-mm2-gray-144836>