



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 185 MM<sup>2</sup>; LATERAL  
MARKER SLOTS; ONLY FOR DIN 35 X 15 RAIL; POWER CAGE CLAMP; 185,00 MM<sup>2</sup>;  
BLUE**

Voltage type 1: AC/DC;

Voltage type 2: DC;

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 1000; V

Tensiune nominala de supratensiune (III/3): 12; kV

Curent nominal: 353; A

Tensiune nominala (III/3) 2: 1500; V

Tensiune nominala de supratensiune (III/3) 2: 12; kV

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: POWER CAGE CLAMP;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Nominal cross-section: 185 mm<sup>2</sup>;

Solid conductor: 50 ... 185 mm<sup>2</sup> / 1/0 AWG ... 350 kcmil;

Stranded conductor: 50 ... 185 mm<sup>2</sup> / 1/0 AWG ... 350 kcmil;

Fine-stranded conductor: 50 ... 185 mm<sup>2</sup> / 1/0 AWG ... 350 kcmil;

Fine-stranded conductor; with insulated ferrule: 50 ... 150 mm<sup>2</sup> / 1/0 AWG ... 300 kcmil;

Fine-stranded conductor; with uninsulated ferrule: 50 ... 185 mm<sup>2</sup> / 1/0 AWG ... 350 kcmil;

Strip length: 45 ... 47 mm / 1.77 ... 1.85 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 32 mm / 1.26 inch;

Inaltime from upper-edge of DIN-rail: 116 mm / 4.567 inch;

Adancime: 133 mm / 5.236 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Marking level: Side marking;  
Culoare: blue;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 535,2; g  
Product Group: 1 (Rail Mounted Terminal Blocks);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4055143067058;  
Customs tariff number: 85369010000;  
Pret: 261,97 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-through-terminal-block-185-mm2-lateral-marker-slots-only-for-din-35-x-15-rail-power-cage-clamp-185-00-mm2-blue-145012>