
www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO TESTING PLUG MODULE WITH CONTACT STUD; FOR 280, 736, 737, 738, 780 SERIES; PIN SPACING 5 MM / 0.197 IN; 2,50 MM²; GRAY

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/2): 250; V
Tensiune nominala de supratensiune (III/2): 2,5; kV
Curent nominal: 0,5; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Tehnologie conexiune: CAGE CLAMP®;
Solid conductor: 0,08 … 2,5 mm² / 28 … 12 AWG;
Fine-stranded conductor: 0,08 … 2,5 mm² / 28 … 12 AWG;
Strip length: 12 … 13 mm / 0.47 … 0.51 inch;
Numar total de conexiuni: 1;
Total number of potentials: 1;
Numar tipuri de conexiuni: 1;
Distanta intre pini: 5 mm / 0.197 inch;
Latime: 5 mm / 0.197 inch;
Inaltime: 14,3 mm / 0.563 inch;
Adancime: 43,45 mm / 1.711 inch;
Test contact length: 17; mm
Application: Testing without connected conductor;
Suitable: for 280, 736, 737, 738, 780 Series;
Culoare: gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);

Contact plating: tin-plated;
Fire load: 0,024; MJ
Greutate: 2,1; g
Temperatura lucru: -60 … +105 °C;
Product Group: 3 (Multi Conn. System);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454193584;
Customs tariff number: 85366990990;
Pret: 19,60 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/testing-plug-module-with-contact-stud-for-280-736-737-738-780-series-pin-spacing-5-mm-0-197-in-2-50-mm2-gray-145237