www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO MODULAR TOPJOB®S CONNECTOR; MODULAR; FOR JUMPER CONTACT SLOT; 1-POLE; 1,50 MM²; GRAY

Tesiune nominala (III/3): 500; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 18; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 15; A
Tensiune nominala UL (Use Group C): 300; V
Curent nominal UL (Use Group C): 15; A
Certificari: UL 1059;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Open Tool Slot;
Connectable conductor materials: Copper;
Nominal cross-section: 1.5 mm²;
Solid conductor: 0.25 … 2.5 mm² / 22 … 14 AWG;
Solid conductor; push-in termination: 0.75 … 2.5 mm² / 18 … 14 AWG;
Fine-stranded conductor: 0.25 … 2.5 mm² / 22 … 14 AWG;
Fine-stranded conductor; with insulated ferrule: 0.75 … 1.5 mm² / 18 … 16 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 0.75 … 1.5 mm² / 18 … 16 AWG;
Strip length: 9 … 11 mm / 0.35 … 0.43 inch;
Numar poli: 1;
Numar total de conexiuni: 1;
Total number of potentials: 1;
Wiring type: Side-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;
Latime: 4.2 mm / 0.165 inch;

Module Latime: 4.2 mm / 0.165 inch;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,07; MJ
Greutate: 2,2; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918975148;
Customs tariff number: 85366990990;
Pret: 11,19 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/modular-topjob-s-connector-modular-for-jumper-contact-slot-1-pole-1-50-mm2-gray-145249