



WAGO MODULAR TOPJOB®S CONNECTOR; MODULAR; FOR JUMPER CONTACT
SLOT; 1-POLE; 1,50 MM²; GRAY

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 18; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group C): 300; V

Curent nominal UL (Use Group C): 15; A

Certificari: UL 1059;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 1.5 mm²;

Solid conductor: 0.25 ... 2.5 mm² / 22 ... 14 AWG;

Solid conductor; push-in termination: 0.75 ... 2.5 mm² / 18 ... 14 AWG;

Fine-stranded conductor: 0.25 ... 2.5 mm² / 22 ... 14 AWG;

Fine-stranded conductor; with insulated ferrule: 0.75 ... 1.5 mm² / 18 ... 16 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0.75 ... 1.5 mm² / 18 ... 16 AWG;

Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;

Numar poli: 1;

Numar total de conexiuni: 1;

Total number of potentials: 1;

Wiring type: Side-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 4.2 mm / 0.165 inch;

Module Latime: 4.2 mm / 0.165 inch;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,07; MJ
Greutate: 2,2; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918975148;
Customs tariff number: 85366990990;
Pret: 11,09 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/modular-topjob-s-connector-modular-for-jumper-contact-slot-1-pole-1-50-mm2-gray-145249>