



WAGO COMPACT TERMINAL BLOCK; FOR CURRENT TRANSFORMER CIRCUIT;
6,00 MM²; MULTICOLOURED

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 6 mm²;

Solid conductor: 0.5 ... 10 mm² / 20 ... 8 AWG;

Solid conductor; push-in termination: 1 ... 10 mm² / 14 ... 8 AWG;

Fine-stranded conductor: 0.5 ... 10 mm² / 20 ... 8 AWG;

Fine-stranded conductor; with insulated ferrule: 2.5 ... 6 mm² / 16 ... 10 AWG;

Fine-stranded conductor; with uninsulated ferrule: 1.5 ... 6 mm² / 16 ... 10 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 2.5 ... 6 mm² / 16 ... 29 AWG;

Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Number of jumper slots: 2;

Inaltime from upper-edge of DIN-rail: 65.3 mm / 2.571 inch;

Adancime: 99.6 mm / 3.921 inch;

Module Latime: 8 mm / 0.315 inch;

Design: angled;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;

Culoare: multicoloured;

Material izolator: Polyamide 66 (PA 66);

Greutate: 299; g

Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143240673;
Customs tariff number: 85369010000;
Pret: 494,78 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/compact-terminal-block-for-current-transformer-circuit-6-00-mm2-multicoloured-145288>