



WAGO 4-CONDUCTOR SHIELD TERMINAL BLOCK; 1,5 MM²; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7,5; PUSH-IN CAGE CLAMP®; 1,50 MM²; WHITE

Ratings per: IEC/EN 60947-7-2;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 1,5 mm²;

Solid conductor: 0,25 ... 2,5 mm² / 22 ... 14 AWG;

Solid conductor; push-in termination: 0,75 ... 2,5 mm² / 18 ... 14 AWG;

Fine-stranded conductor: 0,25 ... 2,5 mm² / 22 ... 14 AWG;

Fine-stranded conductor; with insulated ferrule: 0,75 ... 1,5 mm² / 18 ... 16 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0,75 ... 1,5 mm² / 18 ... 16 AWG;

Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;

Numar total de conexiuni: 4;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Number of jumper slots: 2;

Latime: 4,2 mm / 0.165 inch;

Inaltime from upper-edge of DIN-rail: 32,9 mm / 1.295 inch;

Adancime: 69,9 mm / 2.752 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;

Culoare: white;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,102; MJ

Greutate: 8,3; g

Product Group: 22 (TOPJOB S);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4045454719487;

Customs tariff number: 85369010000;

Pret: 21,75 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-shield-terminal-block-1-5-mm2-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-1-50-mm2-white-145609>