



**WAGO 1-CONDUCTOR MALE CONNECTOR; FEEDTHROUGH FLANGE; 4 MM<sup>2</sup>; PIN  
SPACING 5 MM; 7-POLE; 4,00 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 32; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Nominal cross-section: 4 mm<sup>2</sup>;  
Solid conductor: 0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar poli: 7;  
Numar total de conexiuni: 7;  
Total number of potentials: 7;  
Wiring type: Front-entry wiring;  
Distanta intre pini: 5 mm / 0.197 inch;  
Latime: 49.7 mm / 1.957 inch;  
Inaltime de la fata: 18.3 mm / 0.72 inch;  
Adancime: 40.2 mm / 1.583 inch;  
Tip montaj: Mounting flange;  
Tip contact (pluggable connector): Conector tata/fisa;  
Connector (connection type): for conductors;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,452; MJ  
Greutate: 22,1; g

Product Group: 18 (X-COM-System);  
Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4044918521314;  
Customs tariff number: 85366990990;  
Pret: 30,45 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-male-connector-feedthrough-flange-4-mm2-pin-spacing-5-mm-7-pole-4-00-mm2-gray-146109>