



WAGO 2-CONDUCTOR SHIELD TERMINAL BLOCK; 6 MM²; SUITABLE FOR EX E II APPLICATIONS; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 6,00 MM²; WHITE

Ratings per: IEC/EN 60947-7-2;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 6 mm²;

Solid conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Solid conductor; push-in termination: 2,5 ... 10 mm² / 14 ... 8 AWG;

Fine-stranded conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Fine-stranded conductor; with insulated ferrule: 2,5 ... 6 mm² / 16 ... 10 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 2,5 ... 6 mm² / 16 ... 10 AWG;

Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Number of jumper slots: 2;

Latime: 7,5 mm / 0.295 inch;

Inaltime from upper-edge of DIN-rail: 32,9 mm / 1.295 inch;

Adancime: 57,5 mm / 2.264 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;

Culoare: white;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,154; MJ

Greutate: 17,3; g

Product Group: 22 (TOPJOB S);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4050821189121;

Customs tariff number: 85369010000;

Pret: 22,61 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-shield-terminal-block-6-mm2-suitable-for-ex-e-ii-applications-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-6-00-mm2-white-146268>