



**WAGO MULTILEVEL INSTALLATION TERMINAL BLOCK; 4 MM<sup>2</sup>; CARRIER  
TERMINAL BLOCK WITHOUT KNIFE; P2/P1/PE; BLACK UPPER DECK; BROWN  
MIDDLE DECK; GREEN-YELLOW LOWER DECK; PUSH-IN CAGE CLAMP®; 2,50  
MM<sup>2</sup>; GRAY**

Ratings (note): Potential – ground;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 10; A

Ratings (note) 2: Potential – potential;

Tensiune nominala (III/3) 2: 400; V

Tensiune nominala de supratensiune (III/3) 2: 6; kV

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 250; V

Curent nominal UL (Use Group B): 6,3; A

Tensiune nominala UL (Use Group C): 250; V

Curent nominal UL (Use Group C): 6,3; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group C): 300; V

Curent nominal CSA (Use Group C): 20; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm<sup>2</sup>;

Solid conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;  
Numar total de conexiuni: 5;  
Total number of potentials: 3;  
Numar nivele: 3;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;  
Latime: 5,2 mm / 0.205 inch;  
Inaltime from upper-edge of DIN-rail: 45,2 mm / 1.78 inch;  
Adancime: 110 mm / 4.331 inch;  
Design: angled;  
Tip montaj: DIN-35 rail;  
Potential marking: P2/P1/PE;  
Marking level: Center/side marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,309; MJ  
Greutate: 19,9; g  
Product Group: 22 (TOPJOB S);  
Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4050821464525;  
Customs tariff number: 85369010000;  
Pret: 23,77 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/multilevel-installation-terminal-block-4-mm2-carrier-terminal-block-without-knife-p2-p1-pe-black-upper-deck-brown-middle-deck-green-yellow-lower-deck-push-in-cage-clamp-2-50-mm2-gray-146333>