



WAGO TESTING PLUG MODULE WITH CONTACT STUD; PIN SPACING 5 MM / 0.197
IN; 2,50 MM²; GRAY

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/2): 250; V

Tensiune nominala de supratensiune (III/2): 2,5; kV

Curent nominal: 0,5; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Certificari: UL 1059;

Tehnologie conexiune: CAGE CLAMP®;

Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;

Numar total de conexiuni: 1;

Total number of potentials: 1;

Numar tipuri de conexiuni: 1;

Distanta intre pini: 5 mm / 0.197 inch;

Latime: 5 mm / 0.197 inch;

Inaltime: 14,3 mm / 0.563 inch;

Adancime: 44,45 mm / 1.75 inch;

Test contact length: 18; mm

Application: Testing wired terminal blocks with 0.75 ... 1.5 mm² "f-st" or 0.5 mm² "sol." conductors;

Suitable: for 280, 736, 737, 738, 780 Series;

Culoare: gray;

Material group: I;

Material izolator: Polyamide 66 (PA 66);

Flammability class per UL94: V0;

Clamping spring material: Chrome nickel spring steel (CrNi);

Contact material: Cupru electrolitic(ECu);

Contact plating: tin-plated;
Fire load: 0,024; MJ
Greutate: 1,9; g
Temperatura lucru: -60 ... +105 °C;
Product Group: 3 (Multi Conn. System);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4017332315425;
Customs tariff number: 85366990990;
Pret: 19,42 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/testing-plug-module-with-contact-stud-pin-spacing-5-mm-0-197-in-2-50-mm2-gray-146360>